

## Beam Couplings



| Series            | CL1           | CL2             | CL7                     |
|-------------------|---------------|-----------------|-------------------------|
| Torque Range (Nm) | 0.2-1.8       | 0.5-28          | 0.5-76                  |
| Bore Range (mm)   | 3-8           | 3-19            | 3-30                    |
| Max Speed (rpm)   | 10,000-13,000 | 4,500-10,000    | 2,200-30,000            |
| Mounting Options  | Setscrew      | Setscrew, Clamp | Setscrew, Clamp, Keyway |

## Bellows Couplings



| Series            | CL6             | CL14             |
|-------------------|-----------------|------------------|
| Torque Range (Nm) | 0.8-160         | 13-240           |
| Bore Range (mm)   | 4-42            | 10-38            |
| Max Speed (rpm)   | 4,000-20,000    | 4,500-8,000      |
| Mounting Options  | Setscrew, Clamp | Locking Assembly |

## Disc Couplings



| Series            | CL3     | CL5    | CL9              | CL11         | CL15             | CL18    |
|-------------------|---------|--------|------------------|--------------|------------------|---------|
| Torque Range (Nm) | 2.8-160 | 1-510  | 55-1,000         | 25-15,800    | 50-1,520         | 1.4-510 |
| Bore Range (mm)   | 6-30    | 3-45   | 11-58            | 8-115        | 14-75            | 5-45    |
| Max Speed (rpm)   | 6,000   | 10,000 | 4,500            | 3,400-20,000 | 6,500-18,000     | 10,000  |
| Mounting Options  | Clamp   | Clamp  | Locking Assembly | Keyway       | Locking Assembly | Clamp   |

## Curved Jaw Couplings



| Series            | CL8                     | CL10             | CL16                    | CL17                    | CL19             | CL20                    |
|-------------------|-------------------------|------------------|-------------------------|-------------------------|------------------|-------------------------|
| Torque Range (Nm) | 1.1-860                 | 7.4-760          | 1.1-860                 | 32-860                  | 2.3-150          | 1.1-860                 |
| Bore Range (mm)   | 2-60                    | 8-60             | 3-60                    | 8-60                    | 5-48             | 3-60                    |
| Max Speed (rpm)   | 3,400-19,000            | 4,000-20,000     | 3,400-19,000            | 3,400-13,000            | 4,000-12,000     | 3,400-19,000            |
| Mounting Options  | Setscrew, Clamp, Keyway | Locking Assembly | Setscrew, Clamp, Keyway | Setscrew, Clamp, Keyway | Setscrew, Keyway | Setscrew, Clamp, Keyway |

## Oldham Couplings



| Series            | CL4             |
|-------------------|-----------------|
| Torque Range (Nm) | 0.7-66          |
| Bore Range (mm)   | 4-25            |
| Max Speed (rpm)   | 2,400-9,000     |
| Mounting Options  | Setscrew, Clamp |

## Encoder Couplings



| Series            | CL12-13-15 | CL12-25  | CL12-42  |
|-------------------|------------|----------|----------|
| Torque Range (Nm) | 0.6-1.6    | 1.6      | 2.6      |
| Bore Range (mm)   | 4-6        | 4-10     | 6-14     |
| Max Speed (rpm)   | 6,000      | 6,000    | 4,000    |
| Mounting Options  | Setscrew   | Setscrew | Setscrew |

## Rigid Couplings



| Series            | CL13            |
|-------------------|-----------------|
| Torque Range (Nm) | 0.3-4           |
| Bore Range (mm)   | 3-16            |
| Max Speed (rpm)   | 10,000-23,000   |
| Mounting Options  | Setscrew, Clamp |